



Dipper	A	B	C	C*	D	E	F
1400	5134	<b>3593</b>	<b>3407</b>	<b>3635</b>	2829	5559	5804
1800	5365	<b>3824</b>	<b>3807</b>	<b>4024</b>	3207	5939	6181

\* Maximum dig depth

G	H	I	J	K	L	M	N	O
424	576	1870	2412	1800	1950	4939	1657	353

P	Q	R	S	T*	U	V	W	X
396	400	667	2715	2168	2569	2519	1610	974

mm

### Lifting capacity

These capacities are given for a machine without a bucket or quick-release coupling and fitted with rubber tracks for a 360° total rotation lifted load.

The handling capacity is 75% of the tipping load or 87% of the hydraulic limit.

Caution : In accordance with standard EN 474-5, the machine must be equipped with a safety valve on the boom ram and an overload indicator (available as options) to carry out handling operations.

Outreach (Kg)	1,00 m	1,50 m	2,00 m	2,50 m	3,00 m	3,50 m	4,00 m	4,50 m	5,00 m	Max	Xmax(m)
1400 mm	Z2			1312*	1064*	680*	691	580		497	4.95
	Z1		1642*	1741	1226	946	768	643	551	477	5.05
	Z3	2129*	2417*	1751	1233	948	768	644			
1800 mm	Z2						741*	545*	571	482	5.34
	Z1	1233*	1382*	1799*		911	738	617	526	412	5.43
	Z3	1673*	1929*	1678		908	735	614	525		

\* hydraulic limit

